



**1. SPECIFICATIONS**

(1) Absolute Maximum Rating/极限参数 (Ta=25°C)


Parameter 参数	Symbol 符号	Absolute Maximum Rating 极限参数	Unit 单位
Max Forward current/正向最大电流	If	30	mA
Work Forward Current/工作电流	IF	20	mA
Reverse Voltage/最大反向电压	Vr	5	V
Power Dissipation/损耗功率	Pd	80	mw
Electrostatic Discharge/抗静电电压	HBM	2000	V
Operating Temperature/工作温度范围	Top	-30~+80	°C
Storage Temperature/储存温度范围	Tstg	-40~+100	°C
Lead Soldering Temperature/焊接温度	Tsol	260±5	°C

IFP Conditions: Pulse Width ≤ 10msec and duty ≤ 1/10

(2) Initial Electrical/Optical Characteristics/光电参数 (Ta=25°C)

Parameter 参数	Symbol 符号	Condition 测试条件	Min	Typ	Max	Unit 单位
Forward Voltage / 正向电压	VF	IF=20mA	3.0	3.2	3.4	V
Reverse Current / 反向电流	IR	VR=5V	0	/	5	μA
Viewing Angle / 发光角度	2θ 1/2	IF=20mA	/	45	/	deg
Luminous Intensity / 发光强度	IV	IF=20mA	1500	/	2000	mcd
Luminous Flux/光通量	φ	IF=20mA	/	/	/	lm
Peak Wavelength / 峰值波长	λp	IF=20mA	460	465	470	nm

成品公差±0.1mm



PARTNO/型号	Chip/晶片		Lens Color /外观颜色
	Material/类型	Emitting Color/发光颜色	
512LUBD	InGan/Gan	Blue	Blue

■ **NOTES:**

- All dimension are millimeters
- Tolerance is ±0.25mm unless otherwise noted